

SAFETY DATA SHEET

KOS FIRE CEMENT

Issued: 25/8/10

Page 1

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name: KOS FIRE CEMENT

Product code: PCKOSFIRE / PCKOSBKF

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW ENGLAND

Tel: 0044 113 240 3456 Fax: 0044 113 240 0024

Emergency tel: 0044 113 240 3456 (office hours only)

Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Classification under CHIP: Irritating to eyes.

Classification under CLP: Eye Irrit. 2. Causes serious eye irritation. Skin Irrit. 2. Causes skin irritation.

Workplace exposure limit: This product does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This mixture meets the criteria for classification as dangerous in accordance with

Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: SODIUM SILICATE 1-10%

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Give 1 cup of water to drink every 10 minutes. Consult a

doctor.

Inhalation: No special action required. Ensure patient has a good supply of fresh air

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained

breathing apparatus.

Issued: 25/8/10

SAFETY DATA SHEET

KOS FIRE CEMENT

Page 2

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Scrape up and dispose of as industrial waste

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Respiratory protection not required. in normal use.

Hand protection: Protective gloves.Eye protection: Safety goggles.Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: Buff and Black

Odour: Barely perceptible odour

Evaporation rate: Negligible

Viscosity: Viscous

Relative density: 2-2.5g/cm3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Materials to avoid: Strong acids.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to eyes.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat.

12. ECOLOGICAL INFORMATION

Mobility: Non-volatile.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

PBT identification: This substance is not identified as a PBT substance.

Page 3

KOS FIRE CEMENT

13. DISPOSAL CONSIDERATIONS

Disposal operations: Tipping above or underground (e.g. landfill, etc.).

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION (CHIP)

Hazard symbols: Irritant.



Risk phrases: R36: Irritating to eyes.

Safety phrases: S2: Keep out of the reach of children.

S46: If swallowed, seek medical advice immediately and show this container or label.

Haz. ingredients (label): SODIUM SILICATE

Note: The regulatory information given above only indicates the principal regulations

specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or

provisions.

15. REGULATORY INFORMATION (CLP)

Hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P102: Keep out of reach of children.

SAFETY DATA SHEET

KOS FIRE CEMENT

Page 4

P264: Wash thoroughly after handling.

P337+313: If eye irritation persists: Get medical attention.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+313: If skin irritation occurs: Get medical advice.

P362: Take off contaminated clothing and wash before reuse.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R38: Irritating to skin.

R41: Risk of serious damage to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.